



Revision Number: 002.4

Issue date: 01/31/2023


1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI® FRP-555 Latex FRP Adhesive **IDH number:** 827653
Product type/use: Water based adhesive
Restriction of Use: None identified **Region:** United States
Company address: **Contact information:**
 Henkel Corporation Telephone: +1 (860) 571-5100
 One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center
 Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkeln.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
DANGER: CAUSES SERIOUS EYE IRRITATION.
 MAY CAUSE CANCER.
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
CARCINOGENICITY	1A
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or fumes. Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.
Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If eye irritation persists: Get medical attention.
Storage: Store locked up.
Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Limestone	1317-65-3	30 - 60
Ethylene glycol	107-21-1	1 - 5
Quartz (SiO2), <1% respirable	14808-60-7	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	Move to fresh air in case of accidental inhalation of vapours.
Skin contact:	Wash affected area immediately with soap and water.
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	Consult a physician if necessary. Do not induce vomiting.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Carbon dioxide, foam, powder Water fog.
Special firefighting procedures:	Use water spray to keep fire exposed containers cool and disperse vapors.
Unusual fire or explosion hazards:	Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Do not breathe fumes or dust from this material. Keep out of the reach of children.
Storage:	For safe storage, store at or above 0 °C (32°F) Keep from freezing. Store in a cool, dry area. Keep containers closed when not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. 10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. 5 mg/m3 TWA Respirable fraction. 50 MPPCF TWA Total dust. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None
Ethylene glycol	25 ppm TWA Vapor fraction 50 ppm STEL Vapor fraction 10 mg/m3 STEL Aerosol, inhalable.	None	None	None
Quartz (SiO ₂), <1% respirable	0.025 mg/m3 TWA Respirable fraction.	0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust. 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable.	None	None

Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

Respiratory protection:

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

Eye/face protection:

Safety goggles or safety glasses with side shields.

Skin protection:

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	Off white
Odor:	Mild, Acrylic
Odor threshold:	Not available.
pH:	7.0 - 7.5
Vapor pressure:	15 mm hg (20 °C (68°F))
Boiling point/range:	100 °C (212°F)
Melting point/ range:	Not available.
Specific gravity:	1.42
Vapor density:	Heavier than air
Flash point:	No flashpoint. Aqueous preparation.
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	< 1 (Butyl acetate = 1)
Solubility in water:	Soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	0.02 %; 44.3 g/l (calculated)
Viscosity:	200,000 - 300,000 mPa.s
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	None
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials. Do not freeze.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Inhalation, Skin contact

Potential Health Effects/Symptoms

Inhalation:	May cause irritation to nose and throat. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
Skin contact:	May cause skin irritation.
Eye contact:	Causes serious eye irritation.
Ingestion:	Not expected to be harmful by ingestion. Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Ethylene glycol	Oral LD50 (Rat) = 5.89 g/kg Oral LD50 (Mouse) = 14.6 g/kg Dermal LD50 (Rabbit) = 9,530 mg/kg	Blood, Bone Marrow, Central nervous system, Developmental, Eyes, Irritant, Kidney, Liver, Metabolic
Quartz (SiO ₂), <1% respirable	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Ethylene glycol	No	No	No
Quartz (SiO ₂), <1% respirable	Known To Be Human Carcinogen.	Group 1	Yes

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	None above reporting de minimis. Ammonia, aqueous solution (CAS# 1336-21-6). Ethylene oxide (CAS# 75-21-8). Immediate Health, Delayed Health
CERCLA/SARA Section 311/312:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Ethylene glycol (CAS# 107-21-1).
CERCLA/SARA Section 313:	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 8

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/31/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.