

Version: 3.0 Revision date: 8/28/2024

SAFETY DATA SHEET

Atom Arc 7018-AC

SECTION 1: Identification

1.1. Product identifier

Trade name

Atom Arc 7018-AC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Arc Welding

Restricted to professional users.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

ESAB Welding & Cutting Products

801 Wilson Ave.

PA 17331 Hanover

USA

1-717-637-8911

https://esab.com/us/nam_en/

Contact person

Product Stewardship and Sustainability Team

E-mail

Sustainability@esab.com

SDS date

8/28/2024

SDS Version

3.0

1.4. Emergency telephone number

Contact the poison control at 1-800-222-1222 (24/7) or use the webPOISONCONTROL® (triage.webpoisoncontrol.org) to get specific guidance for your case

See also section 4 "First aid measures".

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Not classified according to HCS (29 CFR 1910.1200)

Version: 3.0 Revision date: 8/28/2024

2.2. Label elements

Hazard pictogram(s)

Not applicable.

Signal word

Not applicable.

Hazard statement(s)

Precautionary statement(s)

General

_

Prevention

-

Response

_

Storage

-

Disposal

-

Additional labelling

Not applicable.

2.3. Other hazards

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Iron	CAS No.: 7439-89-6	60 - 100%		
titanium dioxide	CAS No.: 13463-67-7	7 - 13%	Carc. 2, H351	
limestone	CAS No.: 1317-65-3	5 - 10%		
Calcium fluoride	CAS No.: 7789-75-5	1 - 5%		
Silicic acid, potassium salt	CAS No.: 1312-76-1	1 - 5%		
Manganese	CAS No.: 7439-96-5	0 - 5%		
Silicon	CAS No.: 7440-21-3	0.1 - 1%		
Quartz*	CAS No.: 14808-60-7	0.1 - 1%	STOT RE 1, H372	
Mica	CAS No.: 12001-26-2	0.1 - 1%		

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

_

SECTION 4: First-aid measures

4.1. Description of first aid measures

General information

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

In case of discomfort: bring the person into fresh air.

Skin contact

Upon irritation: rinse with water. In the event of continued irritation, seek medical assistance.

Eye contact

Rinse gently with lukewarm water. Remove any contact lenses if this is easy to do. Continue rinsing. In case of persistent eye irritation or discomfort: Seek medical help.

Ingestion

Rinse and flush mouth thoroughly and consume large quantities of water. In case of continued discomfort: seek medical assistance and bring this safety data sheet.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

None known.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Halogenated compounds

Atom Arc 7018-AC Language: en

Version: 3.0

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Limit spillage, sweep up and shovel into appropriate containers for disposal. Store in suitable, closed containers for disposal.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

No special conditions required.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

No specific requirements

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

titanium dioxide

Long term exposure limit (ACGIH TLV) (mg/m³): 10

Atom Arc 7018-AC Language: en

Version: 3.0



Long term exposure limit (NIOSH REL) (mg/m^3): Potential occupational carcinogen; (ultrafine particles) / 2.4 (fine) / 0.3 (ultrafine)

Version: 3.0

Page 5 of 12

Revision date: 8/28/2024

limestone

Long term exposure limit (OSHA Table Z-1) (mg/m³): 15 (total dust) / 5 (Respirable fraction) Long term exposure limit (NIOSH REL) (mg/m³): 10 (Total dust), 5 (Respirable fraction)

Manganese

Short term exposure limit (STEL) (NIOSH REL) (mg/m³): 3

Long term exposure limit (OSHA Table Z-1) (mg/m³): (Ceiling limit) 5

Long term exposure limit (ACGIH TLV) (mg/m^3): 0.02 (resp.) / 0.1 (Inhalable) / (for elemental and inorganic compounds)

Long term exposure limit (NIOSH REL) (mg/m³): 1

Silicon

Long term exposure limit (OSHA Table Z-1) (mg/m³): 15 (total dust) / 5 (Respirable fraction) Long term exposure limit (NIOSH REL) (mg/m³): 10 (Total dust), 5 (Respirable fraction)

Quartz*

Long term exposure limit (ACGIH TLV) (mg/m³): 0.025 (resp.) for α -quartz and cristobalite Long term exposure limit (NIOSH REL) (mg/m³): Potential occupational carcinogen; 0.05

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and showers are clearly marked.

Hygiene measures

Wash hands after use.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment

Keep your head out of fumes. Use enough ventilation and local exhaust to keep fumes and gases from your breathing zone and the general area. An approved respirator should be used unless exposure assessments are below applicable exposure limits.

Atom Arc 7018-AC Language: en

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R

Hand protection

Wear Protective Gloves

Eye protection

Wear helmet or use face shield with filter lens for open arc welding processes. As a rule of thumb begin with Shade Number 14. Adjust if needed by selecting the next lighter and/or darker shade number. Provide protective screens and flash goggles, if necessary, to shield others from the weld arc flash

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Solid

Color

Various colours

Odor

No relevant or available data due to the nature of the product.

Odor threshold (ppm)

No relevant or available data due to the nature of the product.

рН

No relevant or available data due to the nature of the product.

Density (g/cm³)

No relevant or available data due to the nature of the product.

Kinematic viscosity

Does not apply to solids.

Particle characteristics

No relevant or available data due to the nature of the product.

Phase changes

Melting point/freezing point (°F)

Melting point/freezing point (°C)

>1300

Softening point/range (°F)

Does not apply to solids.

Boiling point (°F)

Does not apply to solids.

Vapor pressure

Version: 3.0

No relevant or available data due to the nature of the product.

Relative vapor density

Does not apply to solids.

Decomposition temperature (°F)

No relevant or available data due to the nature of the product.

Data on fire and explosion hazards

Flash point (°F)

Does not apply to solids.

Flammability (°F)

No relevant or available data due to the nature of the product.

Auto-ignition temperature (°F)

No relevant or available data due to the nature of the product.

Explosion limits (% v/v)

Does not apply to solids.

Solubility

Solubility in water

No relevant or available data due to the nature of the product.

n-octanol/water coefficient (LogKow)

No relevant or available data due to the nature of the product.

Solubility in fat (g/L)

No relevant or available data due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

No relevant or available data due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

Non Reactive unless gets in contact with chemical substances like acids or strong bases could cause generation of gas

Version: 3.0

Page 7 of 12

Revision date: 8/28/2024

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies

None known.

10.4. Conditions to avoid

This product is only intended for normal welding purposes.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products: When this product is used in a welding process, hazardous decomposition

Atom Arc 7018-AC

products would include those from the volatilization, reaction or oxidation of the materials listed in Section 3 and those from the base metal / Coated wire / Coated rod / Bare wire / Bare rod.

Version: 3.0

Page 8 of 12

Revision date: 8/28/2024

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Acute toxicity: Overexposure to welding fumes may result in symptoms like metal fume fever, dizziness, nausea, dryness or irritation of the nose, throat or eye

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

None known.

Other information

titanium dioxide has been classified by IARC as a group 2B carcinogen.

Quartz* has been classified by IARC as a group 1 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

Atom Arc 7018-AC



Version: 3.0 Revision date: 8/28/2024

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)

None of the components are listed

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
DOT	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

^{*} Packing group

Additional information

Not dangerous goods according to DOT, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. U.S. Federal regulations

^{**} Environmental hazards

TSCA (the non-confidential portion)

Iron is listed

titanium dioxide is listed

limestone is listed

Calcium fluoride is listed

Silicic acid, potassium salt is listed

Manganese is listed

Silicon is listed

Quartz* is listed

Clean Air Act

Manganese is regulated as a hazardous air pollutant (HAPS)

EPCRA Section 302

None of the components are listed

EPCRA Section 304

None of the components are listed

EPCRA section 313

Manganese is listed

CERCLA

None of the components are listed

State regulations

California / Prop. 65

None of the components are listed

Massachusetts / Right To Know Act

titanium dioxide is listed

limestone is listed

Manganese is listed

Silicon is listed

Ouartz* is listed

Mica is listed

New Jersey / Right To Know Act

titanium dioxide / Substance number: 1861

limestone / Substance number: 4001

Manganese / Substance number: 1155

Manganese is on the Special Health Hazard Substance List

Silicon / Substance number: 3125

Silicon is on the Special Health Hazard Substance List

Quartz* / Substance number: 1660

Quartz* is on the Special Health Hazard Substance List

Mica / Substance number: 1659

New York / Right To Know Act

titanium dioxide is listed

titanium dioxide is regulated with a Treshold Reporting Quantity (TRQ) of: 100 pounds

Calcium fluoride is listed

Atom Arc 7018-AC

Language: en

Page 10 of 12

Version: 3.0

Revision date: 8/28/2024

Calcium fluoride is regulated with a Treshold Reporting Quantity (TRQ) of: 100 pounds

Manganese is listed

Manganese is regulated with a Treshold Reporting Quantity (TRQ) of: 10 pounds

Pennsylvania / Right To Know Act

titanium dioxide is listed

limestone is listed

Manganese is listed

Manganese is hazardous to the environment (E)

Silicon is listed

Quartz* is listed

Mica is listed

15.4. Restrictions for application

Restricted to professional users.

15.5. Demands for specific education

No specific requirements.

15.6. Additional information

Not applicable.

15.7. Chemical safety assessment

No

15.8. Sources

OSHA Hazard Communication Standard (29 CFR 1910.1200)

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H351, Suspected of causing cancer.

H372, Causes damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

Atom Arc 7018-AC Language: en Version: 3.0



EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

Version: 3.0

Page 12 of 12

Revision date: 8/28/2024

1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

Product Stewardship and Sustainability Team

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en

Atom Arc 7018-AC