



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

#### **SECTION 1. IDENTIFICATION**

Product name : CYCLO CARB CLNR AERO 12/12.50Z

Product code : C1

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone num-

ber

1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : CARB & CHOKE CLEANER

Restrictions on use : Use only outdoors or in a well-ventilated area.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable aerosols : Category 1

Skin irritation : Category 2

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Central nervous system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Neurologic: other (neuropsychological effects, audi-

tory dysfunction and effects on color vision))

Aspiration hazard : Category 1

**GHS** label elements

# CYCLO® CARB CLEANER VOC



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

Hazard pictograms







Signal word : Danger

Hazard statements : Extremely flammable aerosol.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Suspected of damaging the unborn child.

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision))

through prolonged or repeated exposure if inhaled.

### Precautionary statements

#### Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

## Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## Disposal:

Dispose of contents/ container to an approved waste disposal plant.

# CYCLO® CARB CLEANER VOC



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
Acetone	67-64-1	>= 50 - < 70
Toluene	108-88-3	>= 20 - < 30
Heptane, branched, cyclic and linear	426260-76-6	>= 10 - < 20
Carbon dioxide	124-38-9	>= 5 - < 10

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : If on clothes, remove clothes.

Remove contaminated clothing. If irritation develops, get med-

ical attention.

If on skin, rinse well with water.

Wash contaminated clothing before re-use. If skin irritation persists, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Obtain medical attention.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

and effects, both acuited

ıd

This material (or a component) has produced hyperglycemia

and ketosis following substantial ingestion. May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.





Version 3.5

Revision Date: 04/12/2024

SDS Number: 60000001150

Date of last issue: 04/10/2024 Date of first issue: 08/10/2017

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated

exposure if inhaled.

**SECTION 5. FIREFIGHTING MEASURES** 

Suitable extinguishing media : \

Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Product is compatible with standard fire-fighting agents.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec: :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

## **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).





Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling : Open drum carefully as content may be under pressure.

Provide sufficient air exchange and/or exhaust in work rooms.

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges.

Avoid contact with skin and eyes.

Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

No decomposition if stored and applied as directed.

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2





Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
Heptane, branched, cyclic and linear	426260-76-6	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm 9,000 mg/m3	OSHA Z-1
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0

# **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Engineering measures** 

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or

# CYCLO® CARB CLEANER VOC



Version 3.5

Revision Date: 04/12/2024

SDS Number: 60000001150

Date of last issue: 04/10/2024 Date of first issue: 08/10/2017

apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an ap-

proved filter.

In the case of dust or aerosol formation use respirator with an

approved filter.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Wear chemical splash goggles when there is the potential for

exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not smoke. When using do not eat or drink.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : aerosol

Colour : No data available

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -17.8 °C

Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

# CYCLO® CARB CLEANER VOC



Version 3.5 Revision Date: 04/12/2024

SDS Number: 60000001150

Date of last issue: 04/10/2024 Date of first issue: 08/10/2017

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : No data available

Solubility(ies)

Water solubility : slightly soluble

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Molecular weight : No data available

VOC % By Weight : 44 %

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

Carbon oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion

# CYCLO® CARB CLEANER VOC



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

**Acute toxicity** 

Not classified based on available information.

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate: 95.73 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

**Components:** 

Acetone:

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat, female): 76 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 7,426 mg/kg

Toluene:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat, males): 25.7 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12,124 mg/kg

Skin corrosion/irritation

Causes skin irritation.

**Product:** 

Remarks: May cause skin irritation and/or dermatitis.

**Components:** 

Acetone:

Result: Possibly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

Toluene:

Result: Irritating to skin.

Heptane, branched, cyclic and linear:

Result: Irritating to skin.

Carbon dioxide:

Assessment: No skin irritation Result: No skin irritation

# CYCLO® CARB CLEANER VOC



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

## Serious eye damage/eye irritation

Causes serious eye irritation.

### **Product:**

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

## **Components:**

#### Acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

#### Toluene:

Result: Irritating to eyes.

#### Heptane, branched, cyclic and linear:

Result: Possibly irritating to eyes

#### Carbon dioxide:

Result: No eye irritation

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

## Respiratory sensitisation

Not classified based on available information.

## **Components:**

## Toluene:

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Not a skin sensitizer.

### Heptane, branched, cyclic and linear:

Result: Substance is not considered to be potential skin sensitiser.

# Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or





Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Suspected of damaging the unborn child.

### **Components:**

#### Toluene:

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

## STOT - single exposure

May cause drowsiness or dizziness.

#### **Components:**

#### Acetone:

Exposure routes: Inhalation Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

#### Toluene:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

## Heptane, branched, cyclic and linear:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

#### STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on color vision)) through prolonged or repeated exposure if inhaled.

## **Components:**

#### Toluene:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects

on color vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

## Acetone:

May be harmful if swallowed and enters airways.

# CYCLO® CARB CLEANER VOC



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

#### Toluene:

May be fatal if swallowed and enters airways.

#### Heptane, branched, cyclic and linear:

May be fatal if swallowed and enters airways.

#### **Further information**

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## **SECTION 12. ECOLOGICAL INFORMATION**

**Toxicity** 

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

## **SECTION 14. TRANSPORT INFORMATION**

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

## International Regulations

**IATA-DGR** 

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

2.1

203

Labels : Packing instruction (cargo :

aircraft)

Packing instruction : 203

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1950



## CYCLO® CARB CLEANER VOC

Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017

Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## **National Regulations**

**49 CFR** 

UN/ID/NA number : UN 1950 Proper shipping name : Aerosols

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1
ERG Code : 126
Marine pollutant : no

### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Acetone	67-64-1	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Toluene	108-88-3	100	100 (F005)
Benzene	71-43-2	10	10 (D018)
Toluene	108-88-3	1000	3724

## SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

# SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation

Serious eye damage or eye irritation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Toluene 108-88-3 >= 20 - < 30 %

# **CYCLO® CARB CLEANER VOC**



Version Revision Date: SDS Number: Date of last issue: 04/10/2024 3.5 04/12/2024 600000001150 Date of first issue: 08/10/2017


## California Prop. 65

WARNING: This product can expose you to chemicals including Benzene, Ethylbenzene, which is/are known to the State of California to cause cancer, and Toluene, Benzene, n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### **SECTION 16. OTHER INFORMATION**

### **Further information**

## NFPA:



Special hazard

Revision Date : 04/12/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN