

SAFETY DATA SHEET

1. Identification

Product identifier	Duct Seal		
Other means of identification			
SDS number	SDS-00032		
Product code	DX-1, DX-5, DX-5S, DUX 16, DUX 80		
Recommended use	Duct Seal		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Company name Address	ABB Installation Products Inc. 860 Ridge Lake Blvd. Memphis, TN 38120 US		
Telephone	901-252-5000 ext.8324		
E-mail	Not available.		
Emergency phone number	INFOTRAC - 24 HOURS:	1-800-535-5053 +1 352-323-3500 (Outside USA)	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	The mixture does not meet the criteria for classification.	
Precautionary statement		
Prevention	Observe good industrial hygiene practices.	
Response	Wash hands after handling.	
Storage	Store away from incompatible materials.	
Disposal	Dispose of waste and residues in accordance with local authority requirements.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

CAS number	%
1317-65-3	40 - 60
12174-11-7	10 - 15
14807-96-6	5 - 10
	14807-96-6

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.	
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.	
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.	
Duct Seal		S

Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Coughing.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.
6 Accidental release meas	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Following product recovery, flush area with water. Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
_	

7. Handling and storage

Precautions for safe handlingAvoid prolonged exposure. Observe good industrial hygiene practices.Conditions for safe storage,
including any incompatibilitiesStore in tightly closed container. Store away from incompatible materials (see Section 10 of the
SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
Talc (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values	;		
Components	Туре	Value	Form
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable.

Biological limit values	No biological exposure limits noted for the ingredient(s).	
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures, s	such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection		
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.	
Skin protection		
Other	Wear suitable protective clothing.	
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Solid.
Form	Putty-like solid.
Color	Dark gray.
Odor	Not available.
Odor threshold	Not available.
рН	Not applicable
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	310 °C (Cleveland closed cup)
Evaporation rate	Not available.
Flammability (solid, gas)	Non combustible.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not applicable
Flammability limit - upper (%)	Not applicable
Explosive limit - lower (%)	Not applicable
Explosive limit - upper (%)	Not applicable
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	1.78 (water = 1)
Solubility(ies)	
Solubility (water)	Insoluble (< 0.1)
Partition coefficient (n-octanol/water)	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available.
Viscosity	Not applicable
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

Percent volatile

2 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Fluorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.		
Skin contact	Mechanical irritation of skin.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. Coughing.		

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.	
Components	Species	Test Results
Talc (CAS 14807-96-6)		
<u>Acute</u>		
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitizatior	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall I	Evaluation of Carcinogenicity	
Attapulgite (CAS 12174-11-7)		2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
Talc (CAS 14807-96-6)		
NTP Report on Carcinogens	3 Not classifiable as to carcinogenicity to humans.	
Not listed.		
	d Substances (29 CFR 1910.1	001-1053)
Not regulated.	·	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be	harmful.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	
Persistence and degradability	No data is available on the degradability of this product.	
Bioaccumulative potential	No data available.	
Mobility in soil	Expected to have low mobility in soil.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Exp	port Notification (40 CFR 707, Subpt. D)
Not regulated.	
CERCLA Hazardous Su	bstance List (40 CFR 302.4)
Not listed.	
SARA 304 Emergency r	elease notification
Not regulated.	
OSHA Specifically Regu	ulated Substances (29 CFR 1910.1001-1053)
Not Listed.	
Toxic Substances Control Act (TSCA)	One or more components of the mixture are not on the TSCA 8(b) inventory or are designated "inactive".
Superfund Amendments and Re	authorization Act of 1986 (SARA)
SARA 302 Extremely hazard	lous substance
Not listed.	
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting) Not regulated.	
Other federal regulations	
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List
Not regulated	

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Limestone (CAS 1317-65-3) Talc (CAS 14807-96-6)

US. New Jersey Worker and Community Right-to-Know Act

Limestone (CAS 1317-65-3) Talc (CAS 14807-96-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Limestone (CAS 1317-65-3) Talc (CAS 14807-96-6)

US. Rhode Island RTK

Limestone (CAS 1317-65-3) Talc (CAS 14807-96-6)

California Proposition 65



WARNING: This product can expose you to Attapulgite, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

```
Attapulgite (CAS 12174-11-7)
```

Listed: December 28, 1999

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Attapulgite (CAS 12174-11-7) Talc (CAS 14807-96-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	30-November-2015	
Revision date	11-June-2024	
Version	F	
HMIS® ratings	Health: 1	
	Flammability: 0	
	Physical hazard: 0	



Disclaimer

ABB Installation Products Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.