

Oatey Co.

Version No: 1.4

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 03/01/2022 Print Date: 03/01/2022 S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Datey Great Blue Pipe Joint Compound	
Synonyms	Not Available	
Other means of identification	31261, 31262, 31263, 31265	

Recommended use of the chemical and restrictions on use

Relevant identified uses Pipe Thread Sealant

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Oatey Co.
Address	20600 Emerald Parkway, Cleveland, OH 44135 United States Ohio 44135 United States
Telephone	216-267-7100
Fax	Not Available
Website	<u>oatey.com</u>
Email	info@oatey.com

Emergency phone number

Association / Organisation	Chemtrec	
Emergency telephone numbers	1-800-424-9300 (Outside the US 1-703-527-3887)	
Other emergency telephone numbers	1-877-740-5015 (Emergency First Aid)	

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

Classification	Not Applicable

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Not Applicable

Hazard statement(s)

Not Applicable

Frequent or prolonged contact may defat and dry the skin leading to discomfort and dermatitis.

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
13463-67-7*	3-7	Titanium dioxide
64742-52-5*	30-60	Distillates (petroleum), hydrotreated heavy naphthenic
9004-34-6*	1-5	cellulose
1332-58-7*	10-30	Kaolin
14808-60-7*	<0.8	silica crystalline - quartz

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Special protective equipment and precautions for fire-fighters

Fire Fighting	 Alert Fire Department and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use water delivered as a fine spray to control fire and cool adjacent area. Avoid spraying water onto liquid pools. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	 Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. On combustion, may emit irritating/ toxic fumes. May emit acrid smoke. Mists containing combustible materials may be explosive. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Department and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use.
---------------	---

	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	Work clothes should be laundered separately.
	Use good occupational work practice.
	Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium dioxide	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Titanium dioxide	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Titanium dioxide	Titanium dioxide - Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Titanium dioxide	Titanium dioxide	Not Available	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	Titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	(A4)
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Distillates (petroleum), hydrotreated heavy naphthenic	Oil mist, mineral	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	A2
US ACGIH Threshold Limit Values (TLV)	Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil, excluding metal working fluids - Pure, highly and severely refined (Inhalable particulate matter)	5 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	cellulose	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	cellulose	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	cellulose	Cellulose- Total dust	15 mg/m3	Not Available	Not Available	Not Available

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	cellulose	Cellulose- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	cellulose	Cellulose - total	10 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	cellulose	Cellulose - respirable	5 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	cellulose	Cellulose	10 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Kaolin	Inert or Nuisance Dust: Respirable fraction	5 mg/m3 / 15 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	Kaolin	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Kaolin	Kaolin- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	Kaolin	Kaolin- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Kaolin	Kaolin - respirable	5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	Kaolin	Kaolin - total	10 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	Kaolin	Kaolin (Respirable particulate matter)	2 mg/m3	Not Available	Not Available	A4
US OSHA Permissible Exposure Limits (PELs) Table Z-3	silica crystalline - quartz	Silica: Crystalline: Quartz (Respirable)	10 (%SiO2+2) mg/m3 / 250 (%SiO2+5) mppcf	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	silica crystalline - quartz	Silica, crystalline (as respirable dust)	0.05 mg/m3	Not Available	Not Available	Ca; See Appendix A
US ACGIH Threshold Limit Values (TLV)	silica crystalline - quartz	Silica, crystalline - α-quartz and cristobalite (Respirable particulate matter)	0.025 mg/m3	Not Available	Not Available	A2

Exposure controls

Appropriate engineering controls	engineering controls can be highly effective in protecting workers and will typically be independent of workers provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the work that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air course properly. The design of a ventilation system must match the particular process and chemical or contaminant Employers may need to use multiple types of controls to prevent employee overexposure. General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adee Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the work varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to the contaminant. Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air). aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity	ker and ventilation ntaminant if designer i in use. in specific quate protection. place possess
-------------------------------------	--	--

	Within each range the appropriate value depends on:				
	Lower end of the range	Upper end of the range			
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents			
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity			
	3: Intermittent, low production.	3: High production, heavy use			
	4: Large hood or large air mass in motion	4: Small hood-local control only			
	generally decreases with the square of distance from the e extraction point should be adjusted, accordingly, after refer extraction fan, for example, should be a minimum of 1-2 m meters distant from the extraction point. Other mechanical	nce away from the opening of a simple extraction pipe. Velocity xtraction point (in simple cases). Therefore the air speed at the ence to distance from the contaminating source. The air velocity at the /s (200-400 f/min) for extraction of solvents generated in a tank 2 considerations, producing performance deficits within the extraction re multiplied by factors of 10 or more when extraction systems are			
Personal protection					
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 				
Skin protection	See Hand protection below				
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber 				
Body protection	See Other protection below				
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit. 				

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Blue Liquid Paste		
Physical state	Liquid	Relative density (Water = 1)	1.2
Odour	No odor	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	20833.333
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>100	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available

Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	11

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract. Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.
Skin Contact	The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis.
Eye	Direct contact with eyes may cause temporary irritation.
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health; nevertheless exposure by all routes should be minimised as a matter of course.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	×	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend: 💙

— Data either not available or does not fill the criteria for classification
 — Data available to make classification

SECTION 12 Ecological information

Toxicity

Oatey Great Blue Pipe	Endpoint	Test Duration (hr)	Species	Value	Source	
Joint Compound	Not Available	Not Available	Not Available	Not Available	Not Available	

	Endpoint	Test Duration (hr)	Speci	es		Value		Source
	BCF	1008h Fish			<1.1-9.6		7	
	NOEC(ECx)	504h	Crusta	icea		0.02mg/l		4
Titanium dioxide	LC50	96h	Fish			1.85-3.06	img/l	4
	EC50	72h	Algae	or other aquatic pla	ints	3.75-7.58	8mg/l	4
	EC50	48h	Crusta	icea		1.9mg/l		2
	EC50	96h	Algae	or other aquatic pla	ints	179.05mg	g/l	2
	Endpoint	Test Duration (hr)	Spe	cies		Value		Source
	NOEC(ECx)	504h	-	itacea		>1mg		1
Distillates (petroleum), hydrotreated heavy	ErC50	72h			>1000mg/l		1	
naphthenic	EC50	48h	48h Crustacea		>1000)mg/l	1	
	EC50	96h	Alga	e or other aquatic p	lants	>1000)mg/l	1
	Endpoint	Test Duration (hr)		Species	Value		Source	•
cellulose	Not Available	Not Available		Not Available	Not Availab	le	Not Ava	ailable
	Endpoint	Test Duration (hr)		Species	Value		Source)
Kaolin	Not Available	Not Available		Not Available	Not Availab	le	Not Av	ailable
	Endpoint	Test Duration (hr)		Species	Value		Source	•
silica crystalline - quartz	Not Available	Not Available		Not Available	Not Availab	le	Not Av	ailable
Legend:	4. US EPA, Ecoto	IUCLID Toxicity Data 2. Eur x database - Aquatic Toxicit Data 7. METI (Japan) - Bioc	ty Data 5. E	CETOC Aquatic Ha	zard Assessment	•		•

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Titanium dioxide	HIGH	HIGH
cellulose	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
Titanium dioxide	LOW (BCF = 10)
cellulose	LOW (LogKOW = -5.1249)

Mobility in soil

Ingredient	Mobility
Titanium dioxide	LOW (KOC = 23.74)
cellulose	LOW (KOC = 10)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate:

	▶ Reduction
	▶ Reuse
	▶ Recycling
	Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it
	has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life
	considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and
	recycling or reuse may not always be appropriate.
	 DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible or consult manufacturer for recycling options.
	Consult State Land Waste Management Authority for disposal.
	Bury residue in an authorised landfill.
	Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required

Marine Pollutant

NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
Titanium dioxide	Not Available
Distillates (petroleum), hydrotreated heavy naphthenic	Not Available
cellulose	Not Available
Kaolin	Not Available
silica crystalline - quartz	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
Titanium dioxide	Not Available
Distillates (petroleum), hydrotreated heavy naphthenic	Not Available
cellulose	Not Available
Kaolin	Not Available
silica crystalline - quartz	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Titanium dioxide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List US ACGIH Threshold Limit Values (TLV) - Notice of Intended Changes International Agency for Research on Cancer (IARC) - Agents Classified by US DOE Temporary Emergency Exposure Limits (TEELs) the IARC Monographs US List of Active Substances Exempt from the TSCA Inventory Notifications International Agency for Research on Cancer (IARC) - Agents Classified by (Active-Inactive) Rule the IARC Monographs - Group 2B: Possibly carcinogenic to humans US NIOSH Carcinogen List International WHO List of Proposed Occupational Exposure Limit (OEL) US NIOSH Recommended Exposure Limits (RELs) Values for Manufactured Nanomaterials (MNMS) US OSHA Permissible Exposure Limits (PELs) Table Z-1 US - Alaska Air Quality Control - Concentrations Triggering an Air Quality US OSHA Permissible Exposure Limits (PELs) Table Z-3 Episode for Air Pollutants Other Than PM-2.5 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US - California Proposition 65 - Carcinogens US TSCA Chemical Substance Inventory - Interim List of Active Substances US - California Safe Drinking Water and Toxic Enforcement Act of 1986 -Proposition 65 List US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) US ACGIH Threshold Limit Values (TLV) - Carcinogens Distillates (petroleum), hydrotreated heavy naphthenic is found on the following regulatory lists Chemical Footprint Project - Chemicals of High Concern List US ACGIH Threshold Limit Values (TLV) - Carcinogens International Agency for Research on Cancer (IARC) - Agents Classified by US DOE Temporary Emergency Exposure Limits (TEELs) the IARC Monographs US National Toxicology Program (NTP) 15th Report Part A Known to be International Agency for Research on Cancer (IARC) - Agents Classified by Human Carcinogens the IARC Monographs - Group 1: Carcinogenic to humans US OSHA Permissible Exposure Limits (PELs) Table Z-1 US - California Safe Drinking Water and Toxic Enforcement Act of 1986 -US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory Proposition 65 List US TSCA Chemical Substance Inventory - Interim List of Active Substances US ACGIH Threshold Limit Values (TLV) cellulose is found on the following regulatory lists International WHO List of Proposed Occupational Exposure Limit (OEL) US OSHA Permissible Exposure Limits (PELs) Table Z-1 Values for Manufactured Nanomaterials (MNMS) US OSHA Permissible Exposure Limits (PELs) Table Z-3 US - Alaska Air Quality Control - Concentrations Triggering an Air Quality US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory Episode for Air Pollutants Other Than PM-2.5 US TSCA Chemical Substance Inventory - Interim List of Active Substances US - Massachusetts - Right To Know Listed Chemicals US ACGIH Threshold Limit Values (TLV) US NIOSH Recommended Exposure Limits (RELs) Kaolin is found on the following regulatory lists Chemical Footprint Project - Chemicals of High Concern List US NIOSH Recommended Exposure Limits (RELs) International WHO List of Proposed Occupational Exposure Limit (OEL) US OSHA Permissible Exposure Limits (PELs) Table Z-1 Values for Manufactured Nanomaterials (MNMS) US OSHA Permissible Exposure Limits (PELs) Table Z-3 US - Alaska Air Quality Control - Concentrations Triggering an Air Quality US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory Episode for Air Pollutants Other Than PM-2.5 US TSCA Chemical Substance Inventory - Interim List of Active Substances US ACGIH Threshold Limit Values (TLV) US ACGIH Threshold Limit Values (TLV) - Carcinogens silica crystalline - quartz is found on the following regulatory lists Chemical Footprint Project - Chemicals of High Concern List US DOE Temporary Emergency Exposure Limits (TEELs) International Agency for Research on Cancer (IARC) - Agents Classified by US National Toxicology Program (NTP) 15th Report Part A Known to be the IARC Monographs Human Carcinogens International Agency for Research on Cancer (IARC) - Agents Classified by US NIOSH Carcinogen List the IARC Monographs - Group 1: Carcinogenic to humans US NIOSH Recommended Exposure Limits (RELs) US - California Safe Drinking Water and Toxic Enforcement Act of 1986 -US OSHA Carcinogens Listing Proposition 65 List US OSHA Permissible Exposure Limits (PELs) Table Z-3 US - Massachusetts - Right To Know Listed Chemicals US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US ACGIH Threshold Limit Values (TLV) US TSCA Chemical Substance Inventory - Interim List of Active Substances US ACGIH Threshold Limit Values (TLV) - Carcinogens

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	
Gas under pressure	No
Explosive	No

Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	Yes

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including Titanium dioxide which are known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

National Inventory Status

National Inventory	Status
USA - TSCA	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	03/01/2022
Initial Date	02/28/2022

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances