USG

SAFETY DATA SHEET

1. Identification

Product identifier SHEETROCK® Brand Acoustical Sealant

Other means of identification

SDS number 61000040001A

Synonyms Sound Blocking Sealant

Recommended use Interior use.

Recommended restrictionsUse in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

 Telephone
 1-800-874-4968

 Website
 www.usg.com

 Emergency phone number
 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbolNone.Signal wordNone.Hazard statementNone.

Precautionary statement

PreventionObserve good industrial hygiene practices.ResponseGet medical attention/advice if you feel unwell.

Storage Store as indicated in Section 7.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium carbonate, synthetic	471-34-1	> 50
Glycerol	56-81-5	< 5

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation Product cannot be inhaled because it is a paste. When dried, it does not require sanding.Skin contact Rinse area with plenty of water. Get medical attention if irritation develops and persists.

Eye contact Direct contact with eyes may cause temporary irritation. Flush thoroughly with water. If irritation

occurs, get medical assistance.

Ingestion Rinse mouth. Get medical attention if any discomfort occurs.

930857 Version #: 03 Revision date: 10-June-2024 Issue date: 29-October-2015

SDS US

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire fighting

media

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For personal protection, see Section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial

hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

Filled 4.5 gallon pails of sealant may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

Components	r Contaminants (29 CFR 1910.1000) Type	Value	Form
Glycerol (CAS 56-81-5)	PEL	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust.
	mical Hazards Type	Value	Form
US. NIOSH: Pocket Guide to Che Components Calcium carbonate, synthetic (CAS 471-34-1)		Value 5 mg/m3	Form Respirable.

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering controls

SHEETROCK® Brand Acoustical Sealant

Provide sufficient ventilation for operations causing dust formation. Observe occupational

SDS US

exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

2/7

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Skin protection

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator

use.

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Paste.
Color Off-white.
Odor Acrylic.

Odor threshold Not applicable.

pH 8 - 10

Melting point/freezing point Not applicable.

Initial boiling point and boiling Not applicable.

range

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

(%)

Flammability limit - upper

r Not applicable.

(%)

Explosive limit - lower (%) Not applicable.
Explosive limit - upper (%) Not applicable.

Vapor pressure Not applicable.

Vapor density Not applicable.

Relative density 1.6 (H2O=1)

Solubility(ies)

Solubility (water) Miscible with water.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity Not applicable.

Other information

Bulk density13.4 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.VOC< 15 g/l</th>

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Hazardous polymerization does not occur. Possibility of hazardous

reactions

Conditions to avoid None known. Incompatible materials None known.

Hazardous decomposition

products

Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon

dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Inhalation Not relevant, due to the form of the product.

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Eye contact Direct contact with eyes may cause temporary irritation.

May cause discomfort if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Not expected to be a hazard under normal conditions of intended use. **Acute toxicity**

Components **Test Results Species**

Calcium carbonate, synthetic (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/kg

Glycerol (CAS 56-81-5)

Acute

Dermal

LD50 Rabbit > 18700 mg/kg

Oral

LD50 Rat 27200 mg/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

The product contains a small amount of sensitizing substance which may provoke an allergic Skin sensitization

reaction among sensitive individuals after repeated contact. For detailed information, see section

16.

Data does not suggest that this product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

No data available, but none expected.

SHEETROCK® Brand Acoustical Sealant 930857 Version #: 03 Revision date: 10-June-2024 Issue date: 29-October-2015 Specific target organ toxicity -

repeated exposure

No data available, but none expected.

Aspiration hazard

Not an aspiration hazard.

Chronic effects May cause allergic skin disorders in sensitive individuals. For detailed information, see section 16.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Calcium carbonate, synthetic (CAS 471-34-1)

Aquatic

Acute

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 Hours

Glycerol (CAS 56-81-5)

Aquatic Acute

Crustacea EC50 Daphnia magna > 10000 mg/l, 24 Hours

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Partition coefficient n-octanol / water (log Kow)

Glycerol (CAS 56-81-5) -1.76

Mobility in soil No data available.

Other adverse effects None expected.

13. Disposal considerations

Disposal instructions Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

Not applicable.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

930857

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components of this product are in compliance with the listing Requirements of the U.S. Toxic

Substances Control Act (TSCA) Chemical Substance Inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

SHEETROCK® Brand Acoustical Sealant

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Glycerol (CAS 56-81-5)

Other Flavoring Substances with OSHA PEL's

US state regulations

US. Massachusetts RTK - Substance List

Glycerol (CAS 56-81-5)

US. New Jersey Worker and Community Right-to-Know Act

Glycerol (CAS 56-81-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Glycerol (CAS 56-81-5)

US. Rhode Island RTK

Glycerol (CAS 56-81-5)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

Issue date29-October-2015Revision date10-June-2024

Version # 03

Further information Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No.

4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer.

Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with

eczema.

Bucket NFPA Classification:

Health: 0 Flammability: 1 Physical hazard: 0

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings



List of abbreviations NFPA: National Fire Protection Association.

References Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard **Disclaimer**

workers and the environment.

SHEETROCK® Brand Acoustical Sealant

SDS US

930857 Version #: 03 Revision date: 10-June-2024 Issue date: 29-October-2015